

# Application Note: Using Witness Paper - II

## SUMMARY

freETarget has the facility to add witness paper drive to the basic target. Witness paper ensures that there is always a complete target to put holes into and get a reliable shot location. Using witness paper requires four parts:

- Witness Paper Holder and Guide
- Paper Feed
- Paper Feed Switches
- Software Configuration

Each of these topics are discussed separately

This document discusses witness paper drive construction using both DC and Stepper Motor installation. The construction of the drive is described using the DC motor, and the differences in configuration and wiring is detailed in Appendix A

## WITNESS PAPER and GUIDE

Witness paper comes in two widths; 90mm and 165mm. The 90mm width is typically used for rifle shooting, while the 165 is for pistol events. The choice is up to the user, but 90mm is more than sufficient to fill in the black portion of a pistol target.

An example of a paper holder is shown in Figure 1. The witness paper holder is wide enough to fit a 92mm paper roll. This provides a standard 90mm roll with 1mm of clearance on each side. In this example, the witness paper rolls under a round (5mm) bar that lines the paper up with the target. Because of this bar, the witness paper is on a free rolling mount that lets the roll adjust its position as the paper is used.




Figure 1: Witness Paper Holder


## PAPER DRIVE

The paper drive is made from several components.

- Frame ○ Base ○ Left Mount ○ Right Mount
- Motor
- Coupling
- Drive Shaft
- Pinch Rollers



Paper Drive Assembly



Drive Rollers


Figure 3: Motor Coupling

Figure 4: Pinch Roller Bearings

### Construction

In this example, the base is made from 1/4" plywood, and the pinch roller bearings from PVC plastic.

Install the motor mount using four screws






Install the motor using the six mounting screws. Attach the 6mm coupling making sure to line up the flat to the set screw in the coupling. Do not tighten the set


screws just yet.

Slide the left motor mount onto the base plate. It fits very snugly into the groove. This is done to keep everything aligned. You may need to tap into place with a hammer



Insert the drive shaft into the coupling. You may need to adjust the rubber sleeve






Attach the right mount


Attach the mounting screws on both the right and left mounts.


Tighten the set screws on the motor and drive shaft

Assemble the pinch rollers  
Spacer + Roller ...  
Spacer + Locking Collar



Slide the pinch rollers in place






Put the compression springs into both holes.

Use a screwdriver or small knife to push the spring in place.

Hold in place with the 3mm retaining screw



## Testing

Cut a small length of witness paper and insert it into the drive. The slotted hole for the pinch rollers should be long enough that you can move the pinch roller away and slide in the paper. When the pinch rollers are in contact with the drive rollers the witness paper should not be able to be moved.

Apply power to the motor, does the witness paper move easily? You may find that the drive shaft binds in the mounting plates. If this happens, loosen the bolts holding the plates to the mount by  $\frac{1}{2}$  turn.

## Wiring

A control to drive a witness paper roller is provided by the Motor Drive Pin. This pin provides a ground connection through a MOSFET transistor.

The user has the option of turning on a DC motor for a period of time, or issuing pulses to a stepper motor controller. The number of pulses and the pulse duration is available from the setup page on the PC program. The duration of the motor control will be installation dependent and found by trial-and-error

A typical connection for a DC motor is shown in Figure 2.

## Screw Terminal Connector




Figure 2: DC Motor Connection Version 5 Hardware

### IMPORTANT – Feed Direction

The feed direction is determined by the motor polarity and the assembly of the parts. If the paper feed is backwards to the target, reverse the positive and negative motor leads.

**Note: Version 5 hardware includes the switches on the main board.**

# **BILL OF MATERIALS**

Most of the materials on this list were obtained from Amazon simply for convenience. Note that Amazon frequently delivers parts in multiple quantities.

## STEPPER MOTOR INSTALLATION


Version 5 hardware (ESP32) and Version 5.2 and higher software supports witness paper drives using a stepper motor in place of the DC motor described above.

Installing the stepper motor requires the following changes to be made to the wiring and software configuration.

- Wiring – Interfacing to the multifunction connector
- Configuration – Setting the software to drive the stepper motor

### WIRING

The stepper motor interfaces to the FreeTarget circuit using the J1 multifunction connector as illustrated in Figure 8.



J1

Pin	Signal	Description
1	3V3	3.3 Volt (50mA) source to drive the stepper motor interface
2	3V3	3.3 Volt (50mA) source to drive the stepper motor interface
3	A	Multifunction Switch Input A (Sometimes called input 1)
4	G	Digital Ground
5	B	Multifunction Switch Input B (Sometimes called input 2)
6	G	Digital Ground
7	C	Multifunction Switch Input or Output C
8	G	Digital Ground
9	D	Multifunction Switch Input or Output D
10	G	Digital Ground
11	G	Digital Ground

12	G	Digital Ground
----	---	----------------

Figure 8: MultiFunction Connector

The connection between the FreeETarget, the stepper motor drive, and the stepper motor is shown in Figure 9.




Figure 9: Stepper Motor Drive Installation

Typically the FreeETarget uses 3V3 (Pin 1) Ground (Pin 12) and output C (pin 7).

## CONFIGURATION

In order for the stepper motor to operate correctly, the MultiFunction Switches need to be configured to drive the intended output circuit correctly. These are shown in Table 1.

Table 1: Configuration Settings for DC and Stepper Motor Operation

DC Motor Configuration		Stepper Motor Configuration	
{"PAPER_TIME":X}	Time DC motor runs to advance paper in X ms. Typically 500 ms	{"PAPER_TIME":0}	0 indicates DC motor is not used
{"STEP_COUNT":0}	Stepper motor is not used	{"STEP_COUNT":X}	Number of counts (X) to issue to when advancing paper
{"STEP_TIME":0}	Stepper motor is not used	{"STEP_TIME":Y}	Stepper motor clock time (Y) in ms Typically 20ms
		{"MFS_HOLD_C":26}	Use MFS_C as the stepper motor drive

## **WHERE TO BUY WITNESS PAPER Europe**

Kreuger Targets. <https://targets.krueger-shops.eu>

## **North America**

Chase Turner: [krugerpremiumtargets@gmail.com](mailto:krugerpremiumtargets@gmail.com)

Orion Systems: [Paper Roll for Athena NC Models \(orionscoringsystem.com\)](http://Paper Roll for Athena NC Models (orionscoringsystem.com))

Elite Scorer: [Electronic target, Electronic targets shooting, Target scoring system \(elitescorer.com\)](http://Electronic target, Electronic targets shooting, Target scoring system (elitescorer.com))

Targets Canada: <http://www.targets.ca/products/targets-target-systems-and-accessories>

## **Make Your Own Witness Paper**

For true Do-It-Yourself people, there are alternatives to commercially available witness paper


**Black wallpaper** – Available locally in paint supply stores

**Black kraft paper** – Example Amazon, [https://www.amazon.com/RUSPEPA-Black-Kraft-PaperRoll/dp/B07MNVS16/ref=sr\\_1\\_1\\_sspa?crid=2SMOTR3V9LWL0&keywords=black+kraft+paper+roll&qid=1655243454&sprefix=black+Kraft%2Caps%2C80&sr=8-1-spons&psc=1&spLa=ZW5jcnlwdGVkUXVhbGlmaWVyPUFWOUM4TUFGWVVAyNEgmZW5jcnlwdGVkSWQ9QTAzODYxODYzU09YMUg3RFBCUDhSJmVuY3J5cHRIZEfkSWQ9QTAwNTYwODYyQVVO](https://www.amazon.com/RUSPEPA-Black-Kraft-PaperRoll/dp/B07MNVS16/ref=sr_1_1_sspa?crid=2SMOTR3V9LWL0&keywords=black+kraft+paper+roll&qid=1655243454&sprefix=black+Kraft%2Caps%2C80&sr=8-1-spons&psc=1&spLa=ZW5jcnlwdGVkUXVhbGlmaWVyPUFWOUM4TUFGWVVAyNEgmZW5jcnlwdGVkSWQ9QTAzODYxODYzU09YMUg3RFBCUDhSJmVuY3J5cHRIZEfkSWQ9QTAwNTYwODYyQVVO)  
RURKVDA1RU1UJndpZGdIdE5hbWU9c3BfYXRmJmFjdGlvbj1jbGlja1JlZGlyZWN0JmRvTm90TG9nQ2xpY2s9dHJ1ZQ==

**Heat treated cash register paper** – Use standard cash register paper and iron it to turn it black


**Cut down witness paper** – Cut 90mm witness paper in half using a band saw or similar tool  
**Sketch**

**7mm hole Drill Through  
2 Places**



**Left Mount**

**Right Mount**



**Base**